

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 March 2003 (27.03.2003)

PCT

(10) International Publication Number
WO 03/025100 A2

(51) International Patent Classification⁷: **C10L 1/08**

(21) International Application Number: PCT/US02/29402

(22) International Filing Date:
17 September 2002 (17.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/322,757 18 September 2001 (18.09.2001) US

(71) Applicant: **SOUTHWEST RESEARCH INSTITUTE**
[US/US]; Post Office Drawer 28510, San Antonio, TX
78228-0510 (US).

(72) Inventors: **ERWIN, Jimell**; 246 Ridge Drive, San Antonio, TX 78228 (US). **RYAN, III, Thomas, W.**; 13742 Woodpoint Drive, San Antonio, TX 78231 (US). **STANGLMAIER, Rudolf**; 2658 Concan Street, San Antonio, TX 78251 (US).

(74) Agents: **OLIFF, James, A.** et al.; Oliff & Berridge, PLC, P.O. Box 19928, Alexandria, VA 22320 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **FUELS FOR HOMOGENEOUS CHARGE COMPRESSION IGNITION ENGINES**

(57) Abstract: A fuel for a homogeneous charge compression ignition engine having a 95 V% distilled temperature by boiling point measurement in the range of about 35°C to about 350°C, a cetane number in the range of about 2 to about 120, and an octane number in the range of 10 to about 110. The invention also relates to a method of operating a homogeneous charge compression ignition engine of mixing a fuel with air and feeding the fuel into a combustion chamber.

WO 03/025100 A2

FUELS FOR HOMOGENEOUS CHARGE COMPRESSION IGNITION ENGINES

BACKGROUND OF THE INVENTION1. Field of Invention

[0001] This invention relates generally to an internal combustion engine fuel that is used in homogenous charge compression ignition (HCCI) engines, and more particularly to materials that constitute useful fuels for use in HCCI engines and variations for controlling the efficient use of the fuel in the HCCI engines.

2. Description of Related Art

[0002] Air pollution has become one of the more serious problems affecting the United States and other countries, especially in some large urban areas where air pollution has reached critical levels. In the United States, the primary responsibility for setting and maintaining air quality standards rests on the Environmental Protection Agency (EPA). Once the standards are set, the state and local governments are responsible for determining the means of achieving the air pollution standards.

[0003] In the last century, transportation relied primarily upon the internal combustion engine to provide power for mobility. This reliance developed into a mature and well known science in the field of engineering related to the internal combustion engine. Rarely are there "new" concepts for the internal combustion engine because of the advanced stage of engine development, but alternative models are emerging. For instance, an increase in engine power or reduced size/weight may be desired, but may require both increased cost and decreased fuel efficiency of the engine.

[0004] The challenge is to balance the demands of the government in achieving higher fuel efficiency and emissions standards with consumers' demands for high engine power. The traditional vehicle engines are not able to be easily manipulated to achieve a cost-efficient balance of the competing demands. Thus, the search is now to develop new

efficient engines that are able to balance new government standards with consumer demand at a cost-effective level.

[0005] The traditional combustion engines have been either the Diesel or the Otto engines. Although each engine has similar basic structures and workings, the operating properties of each differ greatly.

[0006] The Diesel engine, also known as a reciprocating piston, compression ignition engine, controls the start of combustion by timing the fuel injection. The Otto engine, also known as a rotary internal or spark ignition combustion engine, controls the start of combustion by timing the spark.

[0007] There are advantages and disadvantages of each type of engine or cycle. For example, an Otto cycle system is able to achieve much lower NO_x and particulate emissions level than a diesel engine. These low levels are possible because the Otto cycle engines can take advantage of exhaust gas after treatment systems that will not work on diesel engines. However, Otto cycle engines typically have lower efficiencies than comparable diesel engines.

[0008] The diesel cycle, on the other hand, has a much higher thermal efficiency than the Otto cycle. The diesel cycle uses higher compression ratios than the Otto cycle (which are kept low to avoid "knocking"). The diesel cycle controls the power output without a throttle, therein eliminating throttling losses and achieving higher efficiency at part load. Usually diesel cycle engines do not achieve low NO_x and particulate emissions. The diesel cycle requires a mixing control at a very fuel rich equivalence ratio, thereby resulting in typically higher particulate emissions.

[0009] Considering the disadvantages of each of the traditional combustion cycles, interest is now turning to a type of engine utilizing premixed charge compression ignition (PCCI), also known as homogeneous charge compression ignition (HCCI), active thermo-atmosphere combustion (ATAC), Toyota-Soken (TS), and compression-ignited homogeneous

charge (CIHC). PCCI engines initiate combustion using a well premixed fuel/air mixture that is mixed in the intake port or the cylinder before actual autocompression ignition of the mixture. The actual mixture may vary from being homogeneous to less than homogeneous with some degree of stratification.

[0010] What is desired is a method and system for producing useful and efficient fuels for use in HCCI cycles. It is further desired to have a system for the efficient use of the fuel in a HCCI cycle and therein lower emissions, especially of NO_x and particulate matter.

SUMMARY OF THE INVENTION

[0011] This invention concerns fuels for engines that operate in a homogenous charge compression ignition (HCCI) mode, methods for defining such fuels, for the combustion of these fuels, and for regulating that combustion that engenders the successful and satisfactory operation of HCCI engines.

[0012] The ability of the HCCI engine to develop useful rotary power and to do so with lowered emissions of partially oxidized fuel and soot, and lowered emissions of nitrogen oxides than comparable displacement Otto cycle or diesel cycle depends on a suitably produced fuel. Furthermore, the Otto cycle and the diesel cycle require fuels that exclusively limit the fuel preparation process by relegating available blendstocks to one use or the other thereby restricting the optimal use of available fuel sources. The HCCI engines may use fuels from sources otherwise incompatible if assigned to fuel blends designed for Otto cycle and diesel cycle engines.

[0013] The present invention is directed to overcoming the problems set forth above. This invention sets forth the range of fuel properties for use in HCCI engines and variations for their efficient use as fuel in HCCI engines. Based upon the observations made in numerous experiments of the inventors, specific properties and relations among the properties were discerned and are set forth herein.

[0014] In particular, over 500 engine experiments were performed using a wide variety of fuels in a successful effort to determine the important fuel properties and to define the limits for these properties as specified in this patent.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

[0015] The fuels, deriving from the various exemplary embodiments of the present invention, leave the liquid phase upon introduction into the appropriate locations in the intake manifold or the combustion chamber and become vapor (or gas), or nearly totally vaporize, before the onset of the combustion event. Once exposed through elevation of temperatures and pressure to the conditions required for the onset of autoignition, the air-fuel mixture begins to react and completes combustion before extreme temperatures are reached that lead to greater formation of nitrogen oxides. At the same time, the air-fuel mixture resists the overly rapid combustion that produces premature ignition that is counterproductive and damaging to the engines.

[0016] While there are several different names for this type of process and several different methods available to control and initiate this type of reaction, they all share the common features of premixing some, or all, of the fuel and compression heating initiation of the reaction. This type of reaction will be referred to herein as HCCI irrespective of other names by which it might be called such as Premixed Charge Compression Ignition (PCCI or PMCCI), Controlled Auto Ignition (CAI), Premixed Charge Compression Reaction Engines (PCCRE), and other names. The distinguishing feature of these combustion modes is that a fraction of the fuel is introduced into the combustion chamber prior to the start of combustion, and that this fuel-air mixture is ignited by compression. That is, ignition is achieved without the aid of a spark plug or other active ignition sources (although the use of passive ignition aides such as glow-plugs, surface heaters, or catalytic coatings are covered within the scope of these combustion modes). The fuel can be introduced either upstream of

the intake valves (through carburetors, port-fuel injectors, mixers, etc.), or directly in cylinder through the use of direct fuel injectors.

[0017] The fundamental HCCI characteristics are that a large majority of the fuel is premixed with the air to form a combustible mixture throughout the combustion chamber, and combustion initiates by compression.

[0018] U.S. Patent No. 6,273,076 to Beck et al. (hereinafter "Beck"), incorporated herein in its entirety, describes the general concept of homogeneous charge compression ignition engines and an improved performance by optimizing an excess air ratio and/or intake air charge temperature. However, Beck does not describe or suggest any particular fuels for homogeneous charge compression ignition engines other than identifying that the fuel should be compression ignitable.

[0019] U.S. Patents Nos. 6,276,334 and 6,286,482, both to Flynn et al. and both incorporated herein in their entirety, describe some of the hardware aspects of homogeneous charge compression ignition engines. The Flynn patents also describe a limited number of fuel characteristics and the possible reactivity control achieved by mixing fuels. However, the Flynn patents do not teach any particular fuel properties for homogeneous charge compression ignition engines.

[0020] The HCCI cycle is not greatly affected by the fuel timing delivery as compared to a diesel cycle. The well mixed and nearly homogeneous fuel/air mixture of the HCCI delivers fewer emissions as opposed to the diesel cycle, and offers a potentially excellent fuel efficiency.

[0021] Both the Otto and diesel cycles require fuels exclusively designed for use in their respective engines. HCCI engines, however, require fuels coming from otherwise incompatible fuel blends if designed for Otto or diesel cycles.

[0022] The description of the various exemplary embodiments of the present invention herein are intended to describe the preferred novel fuels for running an HCCI

engine at an optimum level of efficiency and practicality. However, fuels typically fed into Otto cycle engines such as gasoline, having ignition qualities of octane numbers centered on the range of antiknock index 83 to 97 associated with a usual boiling point range of 30°C to 225°C and diesel cycle engines such as a diesel fuel having ignition qualities of cetane numbers centered on the range of 30 to 48 associated with the approximate boiling point range of 175°C to 340°C may also be fed into HCCI engines. However, feeding conventional Otto and diesel cycle fuels into an HCCI engine typically will decrease efficiency of the engine and increase emissions outputs of pollutants. Thus, feeding conventional Otto or diesel cycle fuels into a HCCI cycle engine is not optimal for efficiency and environmental concerns, but can nonetheless be performed.

[0023] Further, various exemplary embodiments of the invention comprise engine cycles wherein there is a single combustion event and multiple combustion events wherein at least one of them can be exemplified as HCCI.

[0024] For the optimum use of the HCCI fuels, the orderly operation of the HCCI engines may depend on which engine configuration is selected. For example, through the careful regulation of the incoming fuel-air charge, including temperature and pressure, an efficient match of the engine operation with the fuel constitution is achieved. Consistent with fuels chosen and operating mode, other governors of combustion may be used including, for example, ignition initiators, auxiliary fuel injectors, compression ratio variation, exhaust gas recirculation (EGR) or inert gas introduction, or variable valve timing strategies to enhance the HCCI engine operation.

[0025] In accordance with various exemplary embodiments of the invention, the properties of the preferred novel HCCI fuels are so arranged to minimize the engine-out or vehicle-out emissions of pollutants including, for example, CO, various hydrocarbons, carbon-containing particles, nitrogen oxides, and the like. Further, the boiling point range, boiling point distribution, volatility, and ignition indices may be configured to simultaneously

minimize the production of the designated pollutants. The engine operating mode to befit these fuel compositions includes, for example, increased intake charge temperature, fuel-air ratio, speed, and intake charge temperature, wherein each is selected to control the onset of combustion and to produce more complete combustion at lower adiabatic flame temperatures.

[0026] In accordance with other various exemplary embodiments of the present invention, the properties of the fuels are so arranged to allow for maximizing the total efficiency of energy production, considering the intrinsic efficiency of the fuels combusting in the engine and the production of the fuels themselves. The specified properties include, for example, but are not limited to, the boiling point range, boiling point distribution, volatility, and ignition indices chosen to incorporate a variety of blendstocks including, for example, petroleum-derived stocks like straightrun naphtha, dehexanizer effluents, cracked stocks, distillate stocks, polymer and other gasoline, and other refinery stocks, whether directly derived from the refinery source or the object of further processing. For example, these may include isomerization and other composition-altering steps; and hydrocarbon stocks like natural gasoline, gasifier liquids, synthesized components whether from degradatory processing, e.g., destructive distillation of natural products or wastes or synthetic processing, e.g., Fischer-Tropsch synthesis or other synthetic processes; non-petroleum sources like alcohols, various oxygenates, and other stocks having more atomic species than carbon and hydrogen; and additive compounds like octane number altering constituents and cetane number changing constituents.

[0027] According to exemplary embodiments of the invention, an internal combustion engine fuel suitable for use in an HCCI mode preferably comprises one or more of the properties listed hereafter.

[0028] The engine fuel can have an evaporative nature or characteristic, sufficient to allow essentially all the fuel in each intake charge to convert to a vapor phase before the onset of combustion. The fuel can have an ignition delay sufficiently long that the onset of

combustion shall be achieved by the engine fuel after the moving piston has exceeded the point of maximum mechanical compression in the movement cycle. Further, the engine fuel may have an ignitability sufficiently high that uniform continuous combustion is achieved throughout the fuel-air charge filling the piston cylinder once ignition commences.

[0029] The preferred engine fuel used in accordance with the exemplary embodiments of the present invention preferably comprises a fuel having:

[0030] (1) a boiling temperature range such that the 95% ASTM D 86 boiling points are about 35°C to about 350°C, preferably about 180°C to about 350°C, more preferably about 225°C to about 350°C;

[0031] (2) a cetane number as measured by ASTM D 613 or similar measurement of ignition characteristics, of about 2 to about 170, preferably 2 to about 70, more preferably 20-70, wherein the cetane number is based on a mixture of hydrocarbons, oxygenates, and/or other major blending components. Further, the cetane number can be, but is not necessarily, influenced by the addition of one or more minor components and/or additives that can change the cetane number;

[0032] (3) an octane number as measured by antiknock index defined in ASTM D 4814 or similar measurement of ignition characteristics, of about 10 to about 110, preferably 12 to about 110, more preferably about 12 to 82, wherein the octane number is based on a mixture of hydrocarbons, oxygenates, and/or other major blending components.

[0033] An alternative method for measuring the ignition characteristics of the fuel embodied in this invention, the elevated pressure autoignition temperature (EPAIT), may also be used to characterize the possible and preferred fuels for HCCI engines. The method is described by Ryan and Matheaus (Ryan, T.W., III and Matheaus, Andrew C., "Fuel Requirements for HCCI Engine Operation", Thiesel 2002, Valencia, Spain, September 11-14, 2002), incorporated herein in its entirety, in its details leading to the present invention. The important characteristics for an HCCI fuel are ignition delay time and temperature at the start

of reaction. Both characteristics are measured in the process of determining EPAIT. The fuels of the invention possess EPAIT in the range of 400°C to 800°C.

[0034] In various exemplary embodiments of the present invention, when the cetane number of the fuel is from about 47 to about 170, the octane number is preferably from about 2 to about 24. In other various exemplary embodiments of the present invention, when the cetane number of the fuel is from about 20 to about 70, the octane number is preferably from about 12 to about 82. In yet other various exemplary embodiments of the present invention, when the cetane number of the fuel is from about 2 to about 20, the octane number is preferably from about 63 to about 110.

[0035] According to exemplary embodiments of the invention, the engine fuel can be utilized to work in combination with one or more engine control and design features including, for example, an engine equipped with variable compression ratio, an engine equipped with variable valve timing, a variable or fixed exhaust gas recirculation (EGR), a variable intake mixture temperature and a variable fuel temperature.

[0036] The systems for controlling the efficient use of the engine fuel can be implemented as a programmed general purpose computer in accordance with exemplary embodiments of the invention. It will be appreciated by those skilled in the art that the controller can be implemented using a single special purpose integrated circuit, for example, an application specific integrated circuit (ASIC), having a main or central processor section for overall, system-level control, and separate sections dedicated to performing various different specific computations, functions and other processes under control of the central processor section. The controller can be a plurality of separate dedicated or programmable integrated or other electronic circuits or devices, e.g., hardwired electronic or logic circuits such as discrete element circuits, or programmable logic devices (PLDs) or the like.

[0037] While the exemplary embodiments of the invention have been described with reference to preferred aspects thereof, it is to be understood that the invention is not

limited to the preferred aspects or constructions. To the contrary, the invention is intended to cover various modifications and equivalent arrangements. In addition, while exemplary aspects of the invention are described, other combinations and configurations are also within the spirit and scope of the invention.

WHAT IS CLAIMED IS:

1. A fuel for a homogeneous charge compression ignition engine having a 95% ASTM D 86 boiling point of about 35°C to about 350°C, a cetane number in the range of about 2 to about 170, and an octane number in the range of about 2 to about 110.
2. The fuel according to claim 1, wherein the 95% ASTM D 86 boiling point is about 180°C to about 350°C.
3. The fuel according to claim 2, wherein the 95% ASTM D 86 boiling point is about 225°C to about 350°C.
4. The fuel according to claim 1, wherein the cetane number is from about 47 to about 170.
5. The fuel according to claim 1, wherein the cetane number is from about 20 to about 70.
6. The fuel according to claim 1, wherein the cetane number is from about 2 to about 20.
7. The fuel according to claim 4, wherein the octane number is from about 2 to about 24.
8. The fuel according to claim 5, wherein the octane number is from about 12 to about 82.
9. The fuel according to claim 6, wherein the octane number is from about 63 to about 110.
10. A fuel for a homogeneous charge compression ignition engine having an elevated pressure autoignition temperature, or an equivalent measure, of about 400°C to about 800°C.
11. A method of operating a homogeneous charge compression ignition engine comprising mixing a fuel with air and feeding the fuel into a combustion chamber of the homogeneous charge compression ignition engine, wherein the fuel comprises a 95% ASTM

D 86 boiling point of about 35°C to about 350°C, a cetane number in the range of about 2 to about 170, and an octane number in the range of about 2 to about 110.

12. The method according to claim 11, wherein the 95% ASTM D 86 boiling point is about 180°C to about 350°C.

13. The method according to claim 12, wherein the 95% ASTM D 86 boiling point is about 225°C to about 350°C.

14. The method according to claim 11, wherein the cetane number is from about 47 to about 170.

15. The method according to claim 11, wherein the cetane number is from about 20 to about 70.

16. The method according to claim 11, wherein the cetane number is from about 2 to about 20.

17. The method according to claim 14, wherein the octane number is from about 2 to about 24.

18. The method according to claim 15, wherein the octane number is from about 12 to about 82.

19. The method according to claim 16, wherein the octane number is from about 63 to about 110.

20. The method according to claim 11, having an elevated pressure autoignition temperature, or an equivalent measure, in the range of 400°C to 800°C.

21. The method according to claim 11, wherein the fuel is controlled by one or more special purpose integrated circuits.

22. A method of operating a homogeneous charge compression ignition engine comprising mixing a fuel with air and feeding the fuel into a combustion chamber of the homogeneous charge compression ignition engine, wherein the fuel comprises a 95% ASTM

D 86 boiling point of about 185°C to about 350°C, a cetane number in the range of about 2 to about 160, and an octane number in the range of 2 to about 103.

23. The method according to claim 16, wherein the feeding of the fuel is controlled by one or more integrated circuits selected from the group consisting of programmable logic devices PLDs, programmable logic arrays PLAs or special purpose control devices.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 March 2003 (27.03.2003)

PCT

(10) International Publication Number
WO 03/025100 A3

(51) International Patent Classification⁷: **C10L 1/08**

(21) International Application Number: **PCT/US02/29402**

(22) International Filing Date:
17 September 2002 (17.09.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/322,757 18 September 2001 (18.09.2001) US

(71) Applicant: **SOUTHWEST RESEARCH INSTITUTE**
[US/US]: Post Office Drawer 28510, San Antonio, TX
78228-0510 (US).

(72) Inventors: **ERWIN, Jimell**; 246 Ridge Drive, San Antonio, TX 78228 (US). **RYAN, III, Thomas, W.**; 13742 Woodpoint Drive, San Antonio, TX 78231 (US). **STANGLMAIER, Rudolf**; 2658 Concan Street, San Antonio, TX 78251 (US).

(74) Agents: **OLIFF, James, A.** et al.; Oliff & Berridge, PLC, P.O. Box 19928, Alexandria, VA 22320 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(88) Date of publication of the international search report:
31 July 2003

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **FUELS FOR HOMOGENEOUS CHARGE COMPRESSION IGNITION ENGINES**

(57) Abstract: A fuel for a homogeneous charge compression ignition engine having a 95 V% distilled temperature by boiling point measurement in the range of about 35°C to about 350°C, a cetane number in the range of about 2 to about 120, and an octane number in the range of 10 to about 110. The invention also relates to a method of operating a homogeneous charge compression ignition engine of mixing a fuel with air and feeding the fuel into a combustion chamber.



WO 03/025100 A3

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/US 02/29402

 A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 C10L1/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

CHEM ABS Data, EPO-Internal, PAJ, WPI Data, API Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 541 835 A (NORTON JOHN H R ET AL) 17 September 1985 (1985-09-17) column 2, line 20 - line 43 column 3, line 42 - line 44	1-23
X	US 4 645 585 A (WHITE NOAM) 24 February 1987 (1987-02-24) table 2	1-9, 11-21
X	NELSON W.L.: "Petroleum refinery engineering" 1958, MCGRAW-HILL, NEW YORK, US XP002238311 4th edition page 56 -page 58; tables 3-19,3-20 -/--	1-9, 11-21

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *A* document member of the same patent family

Date of the actual completion of the international search

16 April 2003

Date of mailing of the international search report

06/05/2003

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Bertin-van Bommel, S

INTERNATIONAL SEARCH REPORT

Internatio plication No
PCT/US 02/29402

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	MAGNUS CHRISTENSEN ET AL.: "Demonstrating the multi-fuel capability of a homogeneous charge compression ignition engine with variable compression ratio" SAE TECHNICAL PAPERS, 25 - 28 October 1999, pages 1-15, XP002238451 US Paper number: 1999-01-3679 page 1, column 1, paragraph 2; table 3 ---	1,11
A	O WIDMAIER: "Kraftstoff für Otto- und Dieselmotoren" BRENNSTOFF-CHEMIE, vol. 50, no. 4, April 1969 (1969-04), pages 97-105, XP008016276 Essen Page 4, Chapter V, Figure 16 ---	1-23
A	US 6 276 334 B1 (AKINYEMI OMOWOLEOLA C ET AL) 21 August 2001 (2001-08-21) cited in the application column 36, line 62 -column 37, line 23 -----	1-23

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 02/29402

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-9,11-21

A fuel having a given 95% ASTM boiling point, cetane number and octane number, and method of operating homogeneous charge compression ignition engine with such a fuel.

2. Claims: 10,22,23

A fuel comprising having a given autoignition temperature and method of operating homogeneous charge compression ignition engine with such a fuel.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International publication No

PCT/US 02/29402

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4541835	A	17-09-1985	AU 536446 B2	10-05-1984
			AU 6463480 A	18-06-1981
			BR 8008034 A	23-06-1981
			CA 1135506 A1	16-11-1982
			DE 3070476 D1	15-05-1985
			EP 0030429 A2	17-06-1981
			JP 1593198 C	14-12-1990
			JP 2019159 B	27-04-1990
			JP 56159290 A	08-12-1981
			JP 1680661 C	13-07-1992
			JP 2245459 A	01-10-1990
			JP 3046663 B	16-07-1991
			NO 803727 A	12-06-1981
			NZ 195644 A	18-11-1983
			US 4541837 A	17-09-1985
			ZA 8006949 A	30-06-1982
			ZW 27980 A1	22-07-1981
			NZ 204850 A	12-11-1986
US 4645585	A	24-02-1987	AU 576776 B2	08-09-1988
			AU 3154784 A	04-03-1985
			WO 8500619 A1	14-02-1985
			CA 1231728 A1	19-01-1988
			DE 3490353 C2	25-07-1996
			DE 3490353 T	08-08-1985
			GB 2155034 A , B	18-09-1985
			JP 5014756 B	25-02-1993
			JP 60501862 T	31-10-1985
			NZ 208911 A	29-04-1988
US 6276334	B1	21-08-2001	ZA 8405472 A	29-05-1985
			BR 9904839 A	18-07-2000
			CN 1263583 T	16-08-2000
			EP 0983433 A1	08-03-2000
			JP 2000513788 T	17-10-2000
			JP 2001020784 A	23-01-2001
			WO 9942718 A1	26-08-1999